

The Mark of Leader
POPULAR[®]
PIPES

U-PVC SOIL, WASTE & VENT SYSTEM

ASTM D-2241, SDR Series
ISO-3633, BS-4514

We have a Solution...



POPULAR PIPES GROUP OF COMPANIES
PROVIDING YOU THE BEST IS OUR FORTE



POPULAR UPVC PRESSURE RATED PIPE AS PER ASTM D-2241, SDR SERIES

Nominal Size	Outer Diameter		SDR-64 (4.3 bar)		SDR 41 (6.9 bar)		SDR 32.5 (8.6 bar)		SDR 26 (11.0 bar)		SDR 21 (13.8 bar)		SDR 17 (17.2 bar)		SDR 13.5 (21.7 bar)	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
INCH	W ALL THICKNESS															
¾"	26.57	26.77	-	-	-	-	-	-	-	-	1.52	2.03	1.57	2.06	1.96	2.49
1"	33.27	33.53	-	-	-	-	-	-	1.52	2.03	1.60	2.11	1.96	2.46	2.46	2.97
1¼"	42.03	42.29	-	-	-	-	1.52	2.03	1.63	2.13	2.01	2.51	2.49	3.00	3.12	3.63
1½"	48.11	48.41	-	-	-	-	1.52	2.03	1.85	2.35	2.29	2.79	2.84	3.35	3.58	4.09
2"	60.17	60.47	-	-	-	-	1.90	2.10	2.31	2.82	2.87	3.38	3.56	4.06	4.47	4.98
3"	88.70	89.10	-	-	2.16	2.67	2.70	3.20	3.43	3.94	4.24	4.75	5.23	5.87	6.58	7.37
4"	114.07	114.53	1.78	2.29	2.79	3.30	3.51	4.01	4.39	4.90	5.44	6.10	6.73	7.54	8.46	9.47
5"	141.05	141.55	2.21	2.72	3.45	3.96	4.34	4.88	5.44	6.12	6.73	7.54	8.31	9.30	10.46	11.71
6"	168.00	168.50	2.64	3.15	4.11	4.62	5.18	5.79	6.48	7.26	8.03	8.99	9.91	11.10	12.47	13.97
8"	218.70	219.46	3.43	3.94	5.33	5.97	6.73	7.54	8.43	9.45	10.41	11.66	12.90	14.45	-	-

POPULAR UPVC PIPES FOR SOIL, WASTE & VENT PURPOSE ISO-3633 & FITTINGS

Mean Outside Diameter	Outer Diameter (mm)	Thickness (mm)		Weight kg/Mtr	
		Type-A	Type-B	Type-A	Type-B
2"	50	Type-A	1.8	Type-A	0.375
		Type-B	3.2	Type-B	0.650
3"	75	Type-A	1.8	Type-A	0.600
		Type-B	3.2	Type-B	1.050
4"	110	Type-A	2.2	Type-A	1.110
		Type-B	3.2	Type-B	1.620
6"	160	Type-A	2.2	Type-A	2.425
		Type-B	3.2	Type-B	3.04

POPULAR UPVC PIPES FOR SOIL, WASTE & VENT PURPOSE BS-4514 & FITTINGS

Nominal Size (Inch)	Outer Diameter (mm)	Thickness (mm)	Weight kg/Mtr
2"	56	3.0	0.820
3"	82	3.2	1.075
4"	110	3.2	1.620
6"	160	3.2	2.25

SALIENT FEATURE

- Non Corrosive
- Non Flammable
- Light Weight
- Insect & Mice Proof
- Free from decomposition
- Resistant to most Chemicals & Acids
- Durable Long Lasting, Glossy & Pleasant Look

SIZE RANGE:

56mm to 160mm with complete Fitting range (BS-4514)

SIZE RANGE:

50mm to 160 mm with complete Fitting range (ISO-3633)



Serving **360°**
of PIPING
Solutions