

The Mark of Leader

POPULAR[®]
PIPES

by p p g

U-PVC Pressure Rated Pipes & fittings

(B,C,D & E Class)
(BS-3505 equivalent to PS-3051/91)

Size Range:
3/4" – 14"

Salient Features

Long Life
High Mechanical Strength
Non Corrosive
Pressure Rated



U-PVC PRESSURE RATED PIPE & FITTINGS

POPULAR U-PVC PRESSURE RATED PIPE AS PER ASTM D-2241, SDR SERIES

NOMINAL SIZE	OUTER DIAMETER		SDR-64 (4.3 bar)		SDR-41 (6.9 bar)		SDR-32.5 (8.6 bar)		SDR-26 (11.0 bar)		SDR-21 (13.8 bar)		SDR-17 (17.2 bar)		SDR-13.5 (21.7 bar)	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
3/4"	26.57	26.77	-	-	-	-	-	-	-	-	1.52	2.03	1.57	2.08	1.98	2.49
1"	33.27	33.53	-	-	-	-	-	-	1.52	2.03	1.60	2.11	1.96	2.46	2.46	2.97
1 1/4"	42.03	42.29	-	-	-	-	1.52	2.03	1.63	2.13	2.01	2.51	2.49	3.00	3.12	3.63
1 1/2"	48.11	48.41	-	-	-	-	1.52	2.03	1.85	2.35	2.29	2.79	2.84	3.35	3.58	4.09
2"	60.17	60.47	-	-	-	-	1.90	2.10	2.31	2.82	2.87	3.38	3.56	4.06	4.47	4.98
3"	88.70	89.10	-	-	2.16	2.67	2.70	3.20	3.43	3.94	4.24	4.75	5.23	5.87	6.58	7.37
4"	114.07	114.53	1.78	2.29	2.79	3.30	3.51	4.01	4.39	4.90	5.44	6.10	6.73	7.54	8.46	9.47
5"	141.05	141.55	2.21	2.72	3.45	3.96	4.34	4.88	5.44	6.12	6.73	7.54	8.31	9.30	10.46	11.71
6"	168.0	168.50	2.64	3.15	4.11	4.62	5.18	5.79	6.48	7.26	8.03	8.99	9.91	11.10	12.47	13.97
8"	218.70	219.46	3.43	3.94	5.33	5.97	6.73	7.54	8.43	9.45	10.41	11.66	12.90	14.45	-	-